

REMOTE INFORMATION WRITING METHOD, REMOTE INFORMATION CHANGING DEVICE AND REMOTE INFORMATION LOADING DEVICE

Publication number: JP7073042 (A)

Publication date: 1995-03-17

Inventor(s): UIRIAMU SHII RATSUSERU; JIYOOJI EI KARUBITSUTSU; ROOREIN EFU BARETSUTO

Applicant(s): CANON INFORMATION SYST INC

Classification:

- **international:** G06F3/00; G06F9/06; G06F9/445; G06F11/00; G06F13/00; H04L29/06; G06F3/00; G06F9/06; G06F9/445; G06F11/00; G06F13/00; H04L29/06; (IPC1-7): G06F9/445; G06F3/00; G06F9/06; G06F13/00

- **European:** G06F9/445E; H04L29/06

Application number: JP19930284598 19931115

Priority number(s): US19920978411 19921118

Also published as:

JP3563751 (B2)

EP0601704 (A1)


US5623604 (A)

DE69323840 (T2)

Abstract of JP 7073042 (A)

PURPOSE: To provide a method and device for remotely changing the programmable firmware of a PROM provided on an interactive network substrate (substrate) equipped with an LAN interface.

CONSTITUTION: An LAN communication program operates the multi-address communication of inquiry through an LAN to a designated substrate, receives substrate position information for the inquiry, and establishes communication with the designated substrate. An ROM firmware image is down-loaded through an LAN interface to the RAM of the designated substrate. The validity of the ROM firmware image stored in the RAM is confirmed. A PROM is controlled so that the storage position is deleted, and preservable data are transmitted from the ROM to the prescribed position of the ROM firmware image stored in the RAM.; After a flash operation, the substrate is reinitialized, and an instruction from the image of the firmware stored in the PROM is executed.



Data supplied from the esp@cenet database — Worldwide